

REACH STACKER SMV 108 TC6

LIFTING DATA			
Lift capacities (at load center LC1 / LC2 / LC3)	10000 kg / 8000 kg / 5000 kg		
Lift capacities (at load center LC1 / LC2 / LC3 at max lifting height)	5000 kg / 5000 kg / 5000 kg		
Load centers (LC1 / LC2 / LC3)	2700 mm / 3850 mm / 6350 mm		
Lifting speed, unloaded / at 40 % load / at 70% rated load	0.55 m/s / 0.53 m/s / 0.40m/s		
Lowering speed, unloaded / at rated load	0.45 m/s / 0.45 m/s		
DRIVING DATA			
Drive speed forward, unloaded / at rated load	30 km/h / 30 km/h		
Drive speed reverse, unloaded / at rated load	30 km/h / 30 km/h		
Incline (driving ability) at rated load at 0 km/h / 2 km/h	29 % / 23 %		
Towing (power ability) at rated load at 0 km/h / 2 km/h	144 kN/ 118 kN		
SERVICE WEIGHT / AXLE PRESSURE			
Service weight	39500 kg		
Axle pressure front at load center LC1, unloaded / at rated load	21800 kg / 38600 kg		
Axle pressure front at load center LC2, unloaded / at rated load	23600 kg / 38900 kg		
Axle pressure rear at load center LC1, unloaded / at rated load	17700 kg / 10900 kg		
Axle pressure rear at load center LC2, unloaded / at rated load	15900 kg / 8600 kg		
Axle pressure in driving position, front/rear (at rated load)	0 kg / 0 kg		
ENGINE (ELECTRONIC CONTROLLED)			
Engine make / model name	Volvo TAD-871-VE	Torque ISO 3046 / at speed	1160 Nm / 1200 rpm
Emission approval EU / US	Stage 4 / Tier 4f	Displacement / No. of cyl. / type	8 l / 6 / Inline
Monitoring / EC / CanBus	Yes / Yes / Yes	Fuel consumption, normal usage	10 - 12 l/h
Fuel / type of engine / intercooler	Diesel / 4-stroke / Yes	Alternator, type/power / capacity	AC / 3080 W / 110 A
Power ISO 3046 / max speed	185 kW / 1600 rpm	Start battery, voltage/capacity	2 x 12 V / 140 Ah
TRANSMISSION (ELECTRONIC CONTROLLED)			
Transmission make / model / amount of gears (forward /reverse)	ZF 4WG-191-B / 4 + 3 gears		
Monitoring / reverse protection / CanBus / Clutch, type	Yes / Yes / Yes / Torque converter		
Transmission type / type of shift gear	Softshift – Powershift / Automatic		
STEERING AXLE & STEERSYSTEM & DRIVE AXLE & BRAKE SYSTEM			
Steer axle type / steering system	Double acting cylinder / hydraulic servo assisted		
Drive axle make / model name	Kessler D81		
Drive axle type / drive axle width	Differential + hub reduction / 4100 mm		
Driving brake system, type / affected wheels	Oil cooled Wet Disc Brakes / drive wheels		
Parking brake system, type / affected wheels	Dry disc brake / spring release / drive wheels		
WHEELS			
Number of wheels, front + rear / type (*driven)	4*+2 / pneumatic		
Tire pressure front / rear	0.90 MPa / 0.90 MPa		
Tire dimensions (Ply rating) front / rear	14.00 x 24" (PR 24) / 14.00 x 24" (PR 24)		
Rim dimension front / rear	10.00 x 24"/HD / 10.00 x 24"/HD		
HYDRAULIC SYSTEM			
Hydraulic pump make / model name	Parker & Hannifin / P2-series		
Hydraulic system / pump type	Load sensing system / variable piston pump		
Power-on-demand / Low energy / Separate oil tanks	Yes / Yes / Yes (hydraulics & brakes)		
Hydraulic oil pressure mast / spreader	23 MPa / 14 MPa		
TANK VOLUMES			
Diesel tank volume	430 l	Hydraulic tank volume	600 l
LIFTING EQUIPMENT & SPREADER			
Spreader make / type	ELME 517-MPS / Toplift (container)		
Spreader functions	20-40 ft containers		
Spreader locking containers + trailer / lifting eyes	4 x top twist locks / 4x in the corners		
Sideshift stroke / rotation / pile slope type (pile slope stroke)	±800 mm / +195 mm: -105 Manual MPS (± 2 deg)		
NORMS & STANDARDS		OTHERS	
Machine Directive in Europe	2006/42/EC	Noise level (inside Cab/ LpAZ)	EN 12053 75 dB(A)
Stability of Industrial Trucks	ISO22915 series / EN15000	Noise level (outside at 7 m/ Lwa)	2000/14/EC 110 dB(A)
Safety of Industrial trucks	ISO 3691-2	Safety, Monitoring & overload system / programmable / colour	Electronic system EMC / Yes / Yes
Noise level (inside Cab / Lm)	DIN 45635 68 dB(A)	Manual sliding cabin / stroke	Yes / (Stepless)

