

Keep on moving  **FORKLIFTCENTER**



40FT 65T Terminal Trailer



GENERAL DESCRIPTION

The Trailer is designed for a maximum payload of 65 tons. It is capable of handling the following containers:

- 1 x 20' or 2 x 20' ISO container
- 1 x 40' ISO container

TECHNICAL SPECIFICATIONS

MODEL :	TTTM4065-21-023		
TYPE:	40FT 65T Terminal Trailer		
DIMENSIONS:			
	Length	12,500 mm	
	Width	2,680 mm	
	Internal Width	2,450 mm	
	Height	1,550 mm	
WEIGHT:			
	Max. Payload	65,000 Kg	
	Tare	7,000 Kg. (Approx)	
	GVW	72,000 Kg.	
SUSPENSION :	FUWA Tandem Heavy duty leaf spring suspension		
AXLES:	02 Nos. FUWA Axles, 10 stud M22 on 335 PCD spigot Capacity : <i>per axle 16 tons at 105 Km/hr.</i>		
CHASSIS:	02 Nos. 500mm x 200mm x 90 Kg/Mtr. High Tensile Steel Mill rolled I-beam with welded Cross members Flange thickness: 15mm, Web Thickness: 10mm		
	Foldable type Bolt on Rear Guide to accommodate 45ft Container Placement	Optional	
CROSS MEMBERS:	250mm x118mm 42 kg/m I-beams		
SIDE GUIDS	High Tensile 14mm plate thick side guides (Bolt On Guides)		
KING PIN :	2" SAE TYPE : Bolted on 10mm skid plate (55 Ton G.C.W.) Set at		



40FT 65T Terminal Trailer



CONTAINER STOPPERS:	02 Nos. Spring Loaded container stoppers	
TYRES:	Pneumatic Tyres 295/80R22.5 Fitted with Rim 22.5x9.00	08 Nos
RIMS :	Rims fitted to tyres 22.5 x 9.00	08 Nos
LANDING LEGS	FUWA 2 speed retractable landing legs with static capacity 80 tons & lift capacity 28 tons	
REAR BUMPER:	Complete with 4 rubber pads	
ELECTRICAL SYSTEM:	24 Volt electrical system (LED). 7 pin electrical connector. Parking, stop, reverse and side marker lights Audible alarm actuates when 'reverse' gear is selected.	
BRAKE SYSTEM:	Air brake system with air tank, emergency relay valve, brake chambers and mechanical slack adjuster	
MARKINGS:	Port identification numbers painted on the side and in front of the trailer and other markings as per customer's request.	
REFLECTORS:	02 Nos. Red triangle reflectors at the rear of the trailer & 4 amber on each side	
ACCESSORIES:	Safety Crash Bar on Either sides of the Trailer	
SHOTBLASTING & PAINTING:	Steel works are shot blasted S.A 2.5 & finished with a multi layer epoxy coating of total DFT 200 microns .Finish layer is in a plain standard RAL Colors code to be chosen by the Customer	
WARRANTY :	Two year comprehensive warranty on complete trailer for factory defects (Except on leaf springs and tyres). 5-year warranty on the paint excluding damages due to abrasion, impact and chemical spillage.	
AFTER SALES :	A comprehensive stock of trailer parts and components are available to maintain all trailers supplied by us	



